

KTMB 183 | Multi-range grommets for KEL 183

for cable diameters 34 - 75 mm / IP54 / UL Type 12



The grommets KTMB-P to KTMB-S are suitable for cable diameters up to 75 mm. These grommets can be used with the [KEL 183 cable entry frames](#).

These multi-range grommets are not split and have a defined area for pushing the cable through.

The blank grommet KTMB-O can accept cable sizes within a specified range. The membrane of the KTMB-O can be pierced or cut (cable diameter minus 10 mm) for cables up to 55mm in diameter.



Specifications


IP rating (EN 60529)	IP54
UL Type (UL 50E)	UL Type 12
Material	Elastomer
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 100 C°
Properties	halogen free, silicone free

Advantages & benefits

- Installation of cables up to 75 mm in diameter
- It is possible to install rigid cables at angles

Product types & sizes


KTMB-O



Part No.	41410
EAN	4251269307133
Package quantity	1
Colour	grey (similar RAL 7035)
Length	91 mm
Width	86 mm
Height	19 mm


Mounting height	2 mm
Blank grommet	1

KTMB-P



Part No.	41415
EAN	4251269307140
Package quantity	1
For max. no. of cables	1
Colour	grey (similar RAL 7035)
Length	91 mm
Width	86 mm

Height	19 mm
Mounting height	2 mm
For cable type	Round cable
Clamping range	1 x 34 - 44 mm


KTMB-Q

Part No.
EAN
Package quantity
For max. no. of cables
Colour
Length
Width

41420
4251269307157
1
1
grey (similar RAL 7035)
91 mm
86 mm

Height
Mounting height
Clamping range

19 mm
2 mm
1 x 44 - 54 mm


KTMB-R

Part No.
EAN
Package quantity
For max. no. of cables
Colour
Length
Width

41425
4251269307164
1
1
grey (similar RAL 7035)
91 mm
86 mm

Height
Mounting height
For cable type
Clamping range

19 mm
2 mm
Round cable
1 x 54 - 64 mm

KTMB-S

Part No.
EAN
Package quantity
For max. no. of cables
Colour
Length
Width

41430
4251269307171
1
1
grey (similar RAL 7035)
91 mm
86 mm

Height
Mounting height
For cable type
Clamping range

19 mm
2 mm
Round cable
1 x 64 - 75 mm