

Rectangular & square punches

sized for heavy multi-pin industrial connectors and icotek cable entry systems



Rectangular and square punches and dies make it easy to punch holes into stainless steel (V2A versions), mild steel, aluminium or plastics with a max. sheet thickness of 2 mm. Available for cut-outs sizes of 10-, 16-, and 24- multi-pin heavy industrial connectors and also for numerous special cut-outs. Therefore, the punches are suitable for most icotek cable entry systems. Centre punches are integrated in the die for exact drilling of mounting holes.

The punches are for hydraulic operation only.

Scope of delivery:

- Punch, die and draw stud
- robust plastic storage case

Note: Punch 125 x 125 mm (order no. 80063) is only to be used with hydraulic foot pump (order no. 80002).

Specifications

Material Steel, hardened and burnished

Advantages & Benefits

- Centre punches for exact drilling of mounting holes
- Robust plastic storage case
- Suitable for hand hydraulic punch driver by icotek and other manufacturers

Product types & Sizes

Punch 24



| | | | |
|-----------------------------------|--|---------------------|----------------------------|
| Part No. | 80053 | Punching material | Plastic, Stahl (St) |
| EAN | 4251269316289 | Max. wall thickness | 2 mm |
| Package quantity | 1 | | |
| Suitable for cable entry systems: | KEL-ER 24, KEL 24, KEL-U 24, KEL-FA 24, KEL-FG A, KEL-FG-ER A, KEL-QUICK 24, KEL-QTA 24, KEL-BES 24, KEL-BES-S 24, KEL-DPZ 24, KEL-DPU 24, KEL-DPU-HD 24, KEL-DP 24 | | |
| Number of center punches | 4 | | |
| Cut-out size | 112 x 36 mm | | |
| Thread UNF | 19 mm | | |

Punch 24 V2A



| | | | |
|-----------------------------------|--|---------------------|------------------------------|
| Part No. | 80153 | Punching material | Stainless steel (V2A) |
| EAN | 4251269316 | Max. wall thickness | 2 mm |
| Package quantity | 1 | | |
| Suitable for cable entry systems: | KEL-ER 24, KEL 24, KEL-U 24, KEL-FA 24, KEL-FG A, KEL-FG-ER A, KEL-QUICK 24, KEL-QTA 24, KEL-BES 24, KEL-BES-S 24, KEL-DPZ 24, KEL-DPU 24, KEL-DPU-HD 24, KEL-DP 24 | | |
| Number of center punches | 4 | | |
| Cut-out size | 112 × 36 mm | | |
| Thread UNF | 19 mm | | |

Punch 24-XL



| | | | |
|-----------------------------------|---|---------------------|----------------------------|
| Part No. | 80054 | Punching material | Plastic, Stahl (St) |
| EAN | 4251269316 | Max. wall thickness | 2 mm |
| Package quantity | 1 | | |
| Suitable for cable entry systems: | KEL-ER 24, KEL 24, KEL-U 24, KEL-FA 24, KEL-FG A, KEL-FG-ER A, KEL-QUICK 24, KEL-BES 24, KEL-BES-S 24, KEL-DPZ 24, KEL-DPU 24, KEL-DPU-HD 24 | | |
| Number of center punches | 4 | | |
| Cut-out size | 112 × 46 mm | | |
| Thread UNF | 19 mm | | |

Punch 24-XL V2A



| | | | |
|--------------|---------------------|-----------|--------------------|
| Part No. | 80154 | Punching | Stainless |
| EAN | 4251269316 | material | steel (V2A) |
| | 463 | Max. wall | 2 mm |
| Package | 1 | thickness | |
| quantity | | | |
| Suitable for | KEL-ER 24, | | |
| cable entry | KEL 24, KEL- | | |
| systems: | U 24, KEL-FA | | |
| | 24, KEL-FG | | |
| | A, KEL-FG-ER | | |
| | A, KEL- | | |
| | QUICK 24, | | |
| | KEL-BES 24, | | |
| | KEL-BES-S | | |
| | 24, KEL-DPZ | | |
| | 24, KEL-DPU | | |
| | 24, KEL-DPU- | | |
| | HD 24 | | |
| Number of | 4 | | |
| center | | | |
| punches | | | |
| Cut-out size | 112 × 46 mm | | |
| Thread UNF | 19 mm | | |

Punch 16



| | | | |
|--------------|---------------------|-----------|-----------------------|
| Part No. | 80052 | Punching | Plastic, Stahl |
| EAN | 4251269316 | material | (St) |
| | 272 | Max. wall | 2 mm |
| Package | 1 | thickness | |
| quantity | | | |
| Suitable for | KEL-ER 16, | | |
| cable entry | KEL 16, KEL- | | |
| systems: | U 16, KEL-FA | | |
| | 16, KEL- | | |
| | QUICK 16, | | |
| | KEL-BES 16, | | |
| | KEL-BES-S | | |
| | 16, KEL-DPZ | | |
| | 16, KEL-DP | | |
| | 16 | | |
| Number of | 4 | | |
| center | | | |
| punches | | | |
| Cut-out size | 86 × 36 mm | | |
| Thread UNF | 19 mm | | |

Punch 16 V2A



| | | | |
|-----------------------------------|--|---------------------|------------------------------|
| Part No. | 80152 | Punching material | Stainless steel (V2A) |
| EAN | 4251269316449 | Max. wall thickness | 2 mm |
| Package quantity | 1 | | |
| Suitable for cable entry systems: | KEL-ER 16, KEL 16, KEL-U 16, KEL-FA 16, KEL-QUICK 16, KEL-BES 16, KEL-BES-S 16, KEL-DPZ 16, KEL-DP 16 | | |
| Number of center punches | 4 | | |
| Cut-out size | 86 × 36 mm | | |
| Thread UNF | 19 mm | | |

Punch 10



| | | | |
|-----------------------------------|--|---------------------|----------------------------|
| Part No. | 80051 | Punching material | Stahl (St), Plastic |
| EAN | 4251269316265 | Max. wall thickness | 2 mm |
| Package quantity | 1 | | |
| Suitable for cable entry systems: | KEL-ER 10, KEL 10, KEL-U 10, KEL-FA 10, KEL-QUICK 10, KEL-QTA 10, KEL-BES 10, KEL-BES-S 10, KEL-DPZ 10, KEL-DP 10 | | |
| Number of center punches | 4 | | |
| Cut-out size | 65 × 36 mm | | |
| Thread UNF | 19 mm | | |

Punch 10 V2A



| | | | |
|--------------|---------------------|-----------|--------------------|
| Part No. | 80151 | Punching | Stainless |
| EAN | 4251269316 | material | steel (V2A) |
| | 432 | Max. wall | 2 mm |
| Package | 1 | thickness | |
| quantity | | | |
| Suitable for | KEL-ER 10, | | |
| cable entry | KEL 10, KEL- | | |
| systems: | U 10, KEL-FA | | |
| | 10, KEL- | | |
| | QUICK 10, | | |
| | KEL-QTA 10, | | |
| | KEL-BES 10, | | |
| | KEL-BES-S | | |
| | 10, KEL-DPZ | | |
| | 10, KEL-DP | | |
| | 10 | | |
| Number of | 4 | | |
| center | | | |
| punches | | | |
| Cut-out size | 65 × 36 mm | | |
| Thread UNF | 19 mm | | |

Punch 6



| | | | |
|--------------|-------------------|-----------|-----------------------|
| Part No. | 80062 | Punching | Plastic, Stahl |
| EAN | 4251269319 | material | (St) |
| | 013 | Max. wall | 2 mm |
| Package | 1 | thickness | |
| quantity | | | |
| Suitable for | KEL-DPZ 6, | | |
| cable entry | KEL-DP 6 | | |
| systems: | | | |
| Number of | 4 | | |
| center | | | |
| punches | | | |
| Cut-out size | 52 × 36 mm | | |
| Thread UNF | 19 mm | | |

Punch 6 V2A



| | | | |
|--------------|-------------------|-----------|--------------------|
| Part No. | 80149 | Punching | Stainless |
| EAN | 4251269321 | material | steel (V2A) |
| | 542 | Max. wall | 2 mm |
| Package | 1 | thickness | |
| quantity | | | |
| Suitable for | KEL-DPZ 6, | | |
| cable entry | KEL-DP 6 | | |
| systems: | | | |
| Number of | - | | |
| center | | | |
| punches | | | |
| Cut-out size | 52 x 36 mm | | |
| Thread UNF | 19 mm | | |

Punch B



| | | | |
|--------------|---------------------|-----------|-----------------------|
| Part No. | 80049 | Punching | Plastic, Stahl |
| EAN | 4251269331 | material | (St) |
| | 831 | Max. wall | 2 mm |
| Package | 1 | thickness | |
| quantity | | | |
| Suitable for | KEL-ER-B, | | |
| cable entry | KEL-B, KEL- | | |
| systems: | U-B, KEL-FG- | | |
| | B, KEL-FG- | | |
| | ER-B, KEL- | | |
| | QUICK-B, | | |
| | KEL-QTA-B, | | |
| | KEL-DPZ-B | | |
| Number of | 4 | | |
| center | | | |
| punches | | | |
| Cut-out size | 46 x 46 mm | | |
| Thread UNF | 19 mm | | |

Punch B

| | | | |
|-----------------------------------|---|---------------------|----------------------------|
| Part No. | 80050 | Punching material | Plastic, Stahl (St) |
| EAN | 4251269316258 | Max. wall thickness | 2 mm |
| Package quantity | 1 | | |
| Suitable for cable entry systems: | KEL-ER-B, KEL-B, KEL-U-B, KEL-FG-B, KEL-FG-ER-B, KEL-QUICK-B, KEL-QTA-B, KEL-DPZ-B | | |
| Number of center punches | - | | |
| Cut-out size | 46 × 46 mm | | |
| Thread UNF | 19 mm | | |

Punch B V2A

| | | | |
|-----------------------------------|---|---------------------|------------------------------|
| Part No. | 80150 | Punching material | Stainless steel (V2A) |
| EAN | 4251269316425 | Max. wall thickness | 2 mm |
| Package quantity | 1 | | |
| Suitable for cable entry systems: | KEL-ER-B, KEL-B, KEL-U-B, KEL-FG-B, KEL-FG-ER-B, KEL-QUICK-B, KEL-QTA-B, KEL-DPZ-B | | |
| Number of center punches | - | | |
| Cut-out size | 46 × 46 mm | | |
| Thread UNF | 19 mm | | |

Punch E5

| | | | |
|--------------|---------------------|-----------|-----------------------|
| Part No. | 80058 | Punching | Plastic, Stahl |
| EAN | 4251269316 | material | (St) |
| | 333 | Max. wall | 2 mm |
| Package | 1 | thickness | |
| quantity | | | |
| Suitable for | KEL-ER-E5, | | |
| cable entry | KEL-E5, KEL- | | |
| systems: | FG-E5, KEL- | | |
| | FG-ER-E5, | | |
| | KEL-QUICK- | | |
| | E5, KEL-FL 4 | | |
| Number of | 2 | | |
| center | | | |
| punches | | | |
| Cut-out size | 112 × 24 mm | | |
| Thread UNF | 19 mm | | |

Punch E4

| | | | |
|--------------|---------------------|-----------|-----------------------|
| Part No. | 80057 | Punching | Plastic, Stahl |
| EAN | 4251269316 | material | (St) |
| | 326 | Max. wall | 2 mm |
| Package | 1 | thickness | |
| quantity | | | |
| Suitable for | KEL-ER-E4, | | |
| cable entry | KEL-E4, KEL- | | |
| systems: | QUICK-E4, | | |
| | KEL-FL 3 | | |
| Number of | 2 | | |
| center | | | |
| punches | | | |
| Cut-out size | 86 × 24 mm | | |
| Thread UNF | 19 mm | | |

Punch E3



| | | | |
|-----------------------------------|---|---------------------|----------------------------|
| Part No. | 80056 | Punching material | Plastic, Stahl (St) |
| EAN | 4251269316319 | Max. wall thickness | 2 mm |
| Package quantity | 1 | | |
| Suitable for cable entry systems: | KEL-ER-E3, KEL-E3, KEL-FG-E3, KEL-FG-ER-E3, KEL-QUICK-E3, KEL-FL 2 | | |
| Number of center punches | 2 | | |
| Cut-out size | 65 x 24 mm | | |
| Thread UNF | 19 mm | | |

Punch E2



| | | | |
|-----------------------------------|---|---------------------|----------------------------|
| Part No. | 80055 | Punching material | Plastic, Stahl (St) |
| EAN | 4251269316302 | Max. wall thickness | 2 mm |
| Package quantity | 1 | | |
| Suitable for cable entry systems: | KEL-ER-E2, KEL-E2, KEL-FG-E2, KEL-FG-ER-E2, KEL-QUICK-E2, KEL-FL 1 | | |
| Number of center punches | 2 | | |
| Cut-out size | 43 x 24 mm | | |
| Thread UNF | 19 mm | | |

Punch E1



| | | | |
|--------------|-------------------|-----------|-----------------------|
| Part No. | 80075 | Punching | Plastic, Stahl |
| EAN | 4251269332 | material | (St) |
| | 517 | Max. wall | 2 mm |
| Package | 1 | thickness | |
| quantity | | | |
| Suitable for | KEL-E1 | | |
| cable entry | | | |
| systems: | | | |
| Number of | 2 | | |
| center | | | |
| punches | | | |
| Cut-out size | 21 x 27 mm | | |
| Thread UNF | 19 mm | | |

Punch 66x112



| | | | |
|--------------|-----------------------|-----------|-------------|
| Part No. | 80061 | Max. wall | 2 mm |
| EAN | 4251269318 | thickness | |
| | 757 | | |
| Package | 1 | | |
| quantity | | | |
| Suitable for | KEL 24-E | | |
| cable entry | | | |
| systems: | | | |
| Number of | - | | |
| center | | | |
| punches | | | |
| Thread UNF | 19 mm | | |
| Punching | Plastic, Stahl | | |
| material | (St) | | |

Punch 125×125

Part No. **80063**
EAN **4251269322709**
Package quantity **1**
Number of center punches -
Thread UNF **19 mm**
Punching material **Plastic, Stahl (St)**
Max. wall thickness **2 mm**



Punch 68×68

Part No. **80064**
EAN
Package quantity **1**
Number of center punches -
Thread UNF **19 mm**
Punching material **Plastic, Stahl (St)**
Max. wall thickness **2 mm**



Punch 92x92



Part No. **80060**
EAN **4251269318**
252
Package quantity **1**
Number of center punches -
Thread UNF **19 mm**
Punching material **Plastic, Stahl (St)**
Max. wall thickness **2 mm**

Punch 22x45



Part No. **80059**
EAN **4251269319**
174
Package quantity **1**
Number of center punches -
Thread UNF **19 mm**
Punching material **Plastic, Stahl (St)**
Max. wall thickness **2 mm**